

# Specification

Size	37.6mm*24mm*5.3mm	BLE version	BLE4.0/BLE5.0/BLE5.1
Material	ABS	Protocol	iBeacon/Eddystone/custom broadcast
Color	White, Black(Other colors can be customized)	OTA	Not supported
Weight	7g (with battery)	Button	N/A
Battery	CR2032 210mAh(replaceable) with battery insulating pull tab	LED	N/A
Battery Life	13 months (Base on Broadcast Interval 1 second and TX power 0dBm)	Sensor	N/A
Transmit range	100 meters in open area	Buzzer	N/A
Reprogrammable	NO (One time programmable)	Working temperature	-40℃~+80℃
Waterproof	N/A	Accessory	1*3M sticker

## Default Parameters(parameters can be customized)

Item	Default setting	Remark
Adv Interval	1000ms (iBeacon), 10s (TLM)	Customizable range: 100-10000ms
Tx Power	0dBm	Customizable range: -40dBm-4dBm
Measure Power	-59dBm	RSSI@1m
Beacon Type	iBeacon+TLM	Customizable Beacon Types: iBeacon, URL, UID, TLM
UUID	(TBD)	
Major	Major and Minor combination is unique	
Minor		
Namespace ID	0x0000000000000000000001	
Serial ID	0x00000000000001	
Eddystone URL		
Password	0000000000000000	

## Product Details

